

A-12M3, A-5CM3 and A-12BM3 13,000 lb. to 24,000 Cap. Two-Post Fore & Aft Lifts (Air-Oil Operated)



ENVIRONMENTALLY FRIENDLY AND SAFE TO OPERATE!

Operates off of Compressed Air and
Non-Vegetable Based Fluid

Just Like That Used by the US Coast Guard



Your Choice of 3 Different Safety Legs:

Spring-Operated
Multi-Position Locking Leg

Standard Automatic
Lock Leg / Non-Rotator

Patented Multi-Position
Locking Legs

Applications:

- Car Dealerships
- Municipalities
- Tire Dealerships
- Brake Shops
- Tune Up Centers
- Service Stations
- Body Shops
- Fleet Service
- Quick Lubes
- Car Collectors
- Scrap Yards
- Anywhere Auto

Manitowoc Lifts offers a full line of in-ground hydraulic lifts to meet your total service repair needs.
All lifts meet or exceed industry standards.

www.manitowoclifts.com

Manitowoc Lifts is an SVI Brand Product Line
SVI International, Inc. • 155 Harvestore Drive DeKalb, IL 60115 • 800-321-8173 • fax: 800-899-1784

A-12M3, A-5CM3 and A-12BM3 13,000 lb. to 24,000 Cap. Two-Post Fore & Aft Lifts (Air-Oil Operated)

Specifications & Ordering Information

FEATURES:

- Removable / Replaceable Plungers
- Manually Ratcheted Front is Standard
- Rear Wheel Wells Insure Proper Rear Alignment
- Low Oil Lock Alerts Operator to a Low Oil Condition
- Front Piston-Casing Assembly is Movable to Accommodate Varying Wheelbases
- Optional Envirokote Polyurea Corrosion Protective Coating
- Floor Level Controls Allow for Operator to Check for Proper Adapter-to-Vehicle Contact
- Standard Track Length is 10 ft. (12 ft. on 2BM3)
Other Lengths Available Up to 18 Ft. (22 Ft. on 2BM3)
- Automatic Safety Locks Standard (Optional Air-Operated, Multi-Position Remote Release Lift Locks on 2BM3)

SPECIFICATIONS	A-12M3	A-5CM3	A-2BM3
Operation:	Full-Hydraulic	Full-Hydraulic	Full-Hydraulic
Capacity:	13,000 lbs.	18,500 lbs.	24,000 lbs.
Front:	6,500 lbs.	6,500 lbs.	12,000 lbs.
Rear:	6,500 lbs.	12,000 lbs.	12,000 lbs.
Rise:	Front: 68" Rear: 70"	Front: 68" Rear: 67"	Front: 65" Rear: 67"
Piston Diameter:	Front: 8-1/2" Rear: 8-1/2"	Front: 8-1/2" Rear: 10-5/8"	Front: 10-5/8" Rear: 10-5/8"
Initial Oil Fill	70 gal.	75 gal.	80 gal.
Oil Displacement	33 gal.	42 gal.	49 gal.
ASME Oil Tank	47 gal.	47 gal.	61 gal.



Made In U.S.A.



SVI International, Inc.
AUTOMOTIVE HYDRAULIC LIFTS
 155 Harvestore Drive
 DeKalb, IL 60115
800-321-8173 • fax: 800-899-1784

www.manitowoclifts.com

Distributed By: