

A-3FM5 and A-7FM6 54,000 lb. to 75,000 lb. Capacity Three-Post Fore & Aft Lifts (Electric-Oil Operated)



ENVIRONMENTALLY FRIENDLY AND SAFE TO OPERATE!

Operates off of Compressed Air and
Non-Vegetable Based Fluid

Just Like That Used by the US Coast Guard

Your Choice of 3 Different Safety Legs:

Spring-Operated
Multi-Position Locking Leg

Standard Automatic
Lock Leg / Non-Rotator

Patented Multi-Position
Locking Legs



Applications:

- Car Dealerships
- Municipalities
- Tire Dealerships
- Brake Shops
- Tune Up Centers
- Service Stations
- Body Shops
- Fleet Service
- Quick Lubes
- Car Collectors
- Scrap Yards
- Anywhere Auto

Manitowoc Lifts offers a full line of in-ground hydraulic lifts to meet your total service repair needs.
All lifts meet or exceed industry standards.

www.manitowoclifts.com

Manitowoc Lifts is an SVI Brand Product Line
SVI International, Inc. • 155 Harvestore Drive DeKalb, IL 60115 • 800-321-8173 • fax: 800-899-1784

A-3FM5 and A-7FM6 54,000 lb. to 75,000 lb. Capacity Three-Post Fore & Aft Lifts (Electric-Oil Operated)

Specifications & Ordering Information

FEATURES:

- Removable / Replaceable Plungers
- Standard Track Length is 12 ft.
Other Lengths Available Up to 22 Ft.
- Front Piston-Casing Assembly is Movable to Accommodate Varying Wheelbases
- Optional Envirokote Polyurea Corrosion Protective Coating
- Floor Level Controls Allow for Operator to Check for Proper Adapter-to-Vehicle Contact
- Air-Operated, Multi-Position Remote Release Lift Locks, Adding Safety and Convenience, Are Standard
- Manually Ratcheted Front is Standard - Optional Hydraulically Driven Front Carriage for Convenience



Height Adapter
(R13323)

For Use on:
A-3FM Series Lifts
 Two (2) are required for each lift. This 9" wide adapter fits R13487 Forward Pickup Slide.

SPECIFICATIONS	A-3FM5	A-7FM6
Operation:	Full-Hydraulic	Full-Hydraulic
Capacity:	54,000 lbs.	75,000 lbs.
Front:	18,000 lbs.	25,000 lbs.
Rear:	36,000 lbs.	50,000 lbs.
Rise:	Front: 65" Rear: 67"	Front: 65" Rear: 67"
Piston Diameter:	Front: 10-5/8" Rear: (2) 10-5/8"	Front: 10-5/8" Rear: (2) 10-5/8"
Initial Oil Fill	115 gal.	115 gal.
Oil Displacement	74 gal.	74 gal.
Power Unit Req.	E04	E05



Made In U.S.A.



SVI International, Inc.
AUTOMOTIVE HYDRAULIC LIFTS
 155 Harvestore Drive
 DeKalb, IL 60115
800-321-8173 • fax: 800-899-1784
 www.manitowoclifts.com

Distributed By: