

OPTIONAL TRACK LENGTHS

For In-Ground Heavy Duty Truck & Bus Fore & Aft Lifts

ENVIRONMENTALLY FRIENDLY AND SAFE TO OPERATE!

Operates off of Compressed Air and Non-Vegetable Based Fluid Just Like That Used by the US Coast Guard

FOR 12M3, 5CM3, 12M5, 6CM5									
TRACK LENGTH									
	10 ft.	11 ft.	12 ft.	13 ft.	14 ft.	15 ft.	16 ft.	17 ft.	18 ft.
"D" DIMENSION									
	145	157	169	181	193	205	217	229	241
"C" DIMENSION									
	129	141	153	165	177	189	201	213	225
MIN. WB	MAXIMUM WHEELBASE								
40	124	136	148	160	172	184	196	208	220
46	130	142	154	166	178	190	202	214	226
52	136	148	160	172	184	196	208	220	232
58	142	154	166	178	190	202	214	226	238
64	148	160	172	184	196	208	220	232	244
70	154	166	178	190	202	214	226	238	250
*76	160	172	184	196	208	220	232	244	256
82	166	178	190	202	214	226	238	250	262
88	172	184	196	208	220	232	244	256	268
94	178	190	202	214	226	238	250	262	272
!100	184	196	208	220	232	244	256	268	280
106	190	202	214	226	238	250	262	274	286
112	196	208	220	232	244	256	268	280	292
118	202	214	226	238	250	262	274	286	298
124	208	220	232	244	256	268	280	292	304
130	214	226	238	250	262	274	286	298	
136	220	232	244	256	268	280	292	304	
142	226	238	250	262	274	286	298		
148	232	244	256	268	280	292	304		
154	238	250	262	274	286	298			
160	244	256	268	280	292	304			
166	250	262	274	286	298				
172	256	268	280	292	304				

* 76" Minimum - 160" Max. Wheelbase Considered Standard 10' Track on 12M3-12M5

! 100" Minimum - 184" Max. Wheelbase Considered Standard 10' Track on 5CM3-6CM5



Manitowoc Lifts offers a full line of in-ground hydraulic lifts to meet your total service repair needs. All lifts meet or exceed industry standards.

www.manitowoclifts.com

Manitowoc Lifts is an SVI Brand Product Line

SVI International, Inc. • 155 Harvestore Drive DeKalb, IL 60115 • 800-321-8173 • fax: 800-899-1784

OPTIONAL TRACK LENGTHS

For In-Ground Heavy Duty Truck & Bus Fore & Aft Lifts

FOR 2BM3, 3BM5, 4BM5, 3FM5, 7FM6									
	10 ft.	11 ft.	12 ft.	13 ft.	14 ft.	15 ft.	16 ft.	17 ft.	18 ft.
	"D" DIMENSION								
	145	157	169	181	193	205	217	229	241
	"C" DIMENSION								
	129	141	153	165	177	189	201	213	225
MIN. WB	MAXIMUM WHEELBASE								
42	122	134	146	158	170	182	194	206	218
48	128	140	152	164	176	188	200	212	224
54	134	146	158	170	182	194	206	218	230
60	140	152	164	176	188	200	212	224	236
66	146	158	170	182	194	206	218	230	242
72	152	164	176	188	200	212	224	236	248
78	158	170	182	194	206	218	230	242	254
84	164	176	188	200	212	224	236	248	260
90	170	182	194	206	218	230	242	254	266
96	176	188	200	212	224	236	248	260	272
!!102	182	194	206	218	230	242	254	266	278
108	188	200	212	224	236	248	260	272	284
114	194	206	218	230	242	264	266	278	290
120	200	212	224	236	248	260	272	284	296
126	206	218	230	242	254	266	278	290	302
132	212	224	236	248	260	272	284	296	308
138	218	230	242	254	266	278	290	302	
144	224	236	248	260	272	284	296	308	
150	230	242	254	266	278	290	302		
156	236	248	260	272	284	296	308		
162	242	254	266	278	290	302			
168	248	260	272	284	296	308			
174	254	266	278	290	302				
180	260	272	284	296	308				

!! 102" Minimum - 206" Max. Wheelbase Considered Standard 12' Track on 2BM3-7FM6



Made In U.S.A.



SVI International, Inc.
AUTOMOTIVE HYDRAULIC LIFTS
 155 Harvestore Drive
 DeKalb, IL 60115
800-321-8173 • fax: 800-899-1784

www.manitowoclifts.com

Distributed By: