

A-22E5A 12,000 lb. Capacity Two-Post Swing Rail Drive-Thru/Over Lift



ENVIRONMENTALLY FRIENDLY AND SAFE TO OPERATE!

Operates off of Compressed Air and
Non-Vegetable Based Fluid

Just Like That Used by the US Coast Guard

Applications:

- Car Dealerships
- Municipalities
- Tire Dealerships
- Brake Shops
- Tune Up Centers
- Service Stations
- Body Shops
- Fleet Service
- Quick Lubes
- Car Collectors
- Scrap Yards
- Anywhere Auto

MODEL A-22E5A



Your Choice of 3 Different Safety Legs:

Spring-Operated
Multi-Position Locking Leg

Standard Automatic
Lock Leg / Non-Rotator

Patented Multi-Position
Locking Legs

E04 Power Unit

Manitowoc Lifts offers a full line of in-ground hydraulic lifts to meet your total service repair needs. All lifts meet or exceed industry standards.

Manitowoc Lifts is an SVI Brand Product Line
SVI International, Inc. • 155 Harvestore Drive DeKalb, IL 60115 • 800-321-8173

A-22E5A 12,000 lb. Capacity

Two-Post Swing Rail Drive-Thru/Over Lift

Specifications & Ordering Information

FEATURES:

- Wall Control Valves Included
- Solid Steel Arms and Bolsters
- Removable/Replaceable Plungers
- Large Diameter Bearing for Greater Stability
- Oil Flow Control Orifice Protects Against Rapid Descent
- Multi-Position Automatic Safety Locks
- EnviroKote Polyurea Coated
- 77 1/2" Drive-Thru Width Allows Ample Tire Clearance For Safe, Sure Spotting
- Reversible Drive-Thru/Over Superstructure and Alignment Superstructure Ready for Greater Versatility
- 72" Rise
- Four-Position Adapter Pads Permit Varying Heights for Accessibility
- Rugged Rack and Pinion Assembly Equalizes Both Pistons



Made In U.S.A.

SPECIFICATIONS		A-22E5A
Operation:	Full Hydraulic	
Capacity (lbs.):	12,000	
Rise Height:	81-3/4"	
Piston Diameters:	8-1/2"	
Piston Centers:	57-1/2"	
Speed Of Rise:	53 sec.	
Electric Oil Unit - E04:	7-1/2 hp 3 ph or 1 ph	
Tank Size:	46" x 34" x 27" 100 gal.	
ADAPTER HEIGHTS		
	From Floor	From Top of Arm
	4-3/8"	1-3/8"
	6"	3"
	6-5/8"	3-5/8"
	10"	7"



155 Harvestore Drive • DeKalb, IL
800-321-8173

Distributed By: